



HONGKONG KOON TECHNOLOGY LIMITED

268#,Nangchang industrial park, Gushu, Baoan district, Shenzhen, China

Tel: 0086755 29116322 ect 8005 Fax:0086755 29790278

Email: jenny@koontech.com

www.koontech.com



Analog KNSP-26-A-BK Waterproof Telephone

DESCRIPTION ITEM NO.

1. Robust PP alloy material, Vandal & tamper-resistant hardware, easy Installation.
2. Waterproof rating IP66 dust proof.
3. Without keypad, 1 button programmable telephone
4. Magnetic reed hook-switch.
5. Lightning protection to ITU-T recommendation K.21.
6. Heavy Duty handset with hearing Aid compatible(HAC) receiver, Noise canceling microphone.
7. Handset with industrial strong curly cord .
8. Door cover: orient automatically and good self - closing, convenient for use.
9. Temperature range from -40 degree to +70 degree.
10. Support echo cancellation.
11. Optional 7 minute time-limited call.(This function upon buyer's requirement).
12. Application: Tunnel, metro, railway, LRT, speedway, marine, ship, offshore, mine, power plant, bridge etc.



SPECIFICATION

1. PSTN analog telephone
 2. DTMF dialing
 3. MTBF:100000hours
 4. MTTR: 2 hours
 5. Connection: RJ11 screw terminal pair cable
 6. Applicable for various types of SPC exchange PABX and dispatching exchange system with feeding voltage of 24--60V.
 7. Sound level of ringing:over 80dB @50CM.
 8. Standard frequency:
 - high frequency group level: -7 ± 3 dB
 - Low frequency group level: -9 ± 3 dB
 - frequency combination, high and low level difference: 2 ± 1 dB
 - low frequency group : 697. 770. 852. 941Hz,
 - high frequency group : 1209. 1336. 1477Hz,
 - frequency deviation : $-1.5\% \sim +1.5\%$
 9. Call transmission index:
 - SLR<12, RLR<-1, STMR>10, output impedance is 600 Ohm. maximum distance: 7KM
- Electro acoustic characteristics:
- Sending Loudness Rating : $\geq +2$ dB $\leq +12$ dB
 - Receiving Loudness Rating : ≥ -8 dB ≤ -1 dB
 - Sidetone Loudness Rating : $\geq +3$ dB $\geq +10$ dB
10. Super strong function is available for dialing
 11. groups of numbers stored in the memory (maximum length of each number is 16 digits)
 12. Connection: RJ11 screw terminal pair cable (or RJ11 Socket of plug upon request)

Order information:

Model number	Item Number
KNSP-26-A-BK	

CERTIFICATION

EN55022: emissions EN55024: immunity
 Ingress Protection: GB4208-93 IP66 FCC ITU-T Recommendations K21
 EMC: EN50121(Railway application-Electromagnetic Compatibility)



Description :

The portable telephone use along the track (Direct telephone line). The telephone like a portable mobile will be provided without keypad. It is hot line phone. It come with a button to switch on and switch off the line. It is weather protected IP67. The call start when handset receiver is connected and after the operator press on the button of call. The call stop when one or the other of the speaker hangs up again.

Easy operation:

open the door-->plug the connect plug into a proper telephone socket--> pick the handset and press the call button--> speaking--> hang up--> close the door.



PACKAGING

Unit size:275 *220*160mm Unit: N.W:2.2KG

1pcs packing box size: 275 *235 *180mm Unit N.W:2.7KG

4pcs in 1 outer Carton box: size: 500*300*410 mm N.W:8.5KG