

## Audible and Visual Alarm D7



### Application

Widely used in oil exploration, refining, chemical, military, and other hazardous environments and offshore oil platforms, oil tankers and other places for general lighting and task lighting purposes;

Suitable for energy-saving projects and repair and replacement places;

Suitable for higher protection requirements, moist places;

Suitable for explosive gas atmospheres of Zone 1, Zone 2 locations;

Applicable II A, II B, II Class C explosive gas atmospheres;

Suitable for temperature class T1-T6 group

### Features

Aluminum die-cast shell, surface electrostatic spray.

Glass shade, with a strong impact resistance.

High corrosion resistance of stainless steel exposed fasteners;

LED light source, high brightness, long service life.

Pipe or cable wiring.

### Technical Specification

Model: Beacon-7

Ex-mark: Exd[ib]ib II CT6/DIP A20 TA, T6

Rated voltage: AC220V 50Hz (if any special requirements please specify)

Protection class: IP66

Corrosion grade: WF1 \* WF2

Flash Views: 150 times / min

Sound intensity:  $\geq 120\text{dB}$

Intakes specifications: G3 / 4 ", suitable for  $\Phi 10\text{mm} \sim \Phi 14\text{mm}$  cable

Terminals:  $\leq 2.5\text{mm}^2$

Installation: pedestal (z),

Product Weight: 2.56kg

### Dimension (mm)

