

KNEM-30 SOS Emergency Intercom Station

DESCRIPTION ITEM NO.ZD09A0022


1. Cold-roll steel body, vandal & tamper-resistant hardware, easy Ground installation.
2. Waterproof rating IP65~66 dust proof.
3. Built-in loudspeaker 30W for PA.
4. Hands-free backlit buttons(Optional), Built-in 3W speaker, Mic; full duplex communication.
5. Lightening protection to ITU-T recommendation K.21.
6. AC110~240V powered (Optional).
7. Temperature range from -40 degree to +70 degree.
8. Support echo cancellation.
9. Remote software upgrade, configuration and monitoring.
10. Optional 7 minute time out to release the line if the handset is left off hook . This function upon buyer's requirement).
11. Powder coated in UV stabilized polyester finish.
12. The housing covered with a layer of reflective label for easy identification at night.Optional
13. Application: Tunnel, metro, railway, LRT, speedway, marine, ship,offshore, mine, power plant, bridge etc.


SPECIFICATION

VoIP SIP2.0 telephone DTMF dialing
 MTBF: 100000hours MTRR: 2 hours
 Hotline(maximum length of each number is 16 digits)
 Communication: Full duplex 2-way hands-free communication
 Call Control Signaling:VOIP SIP Info(DTMF), RFC 2833(DTMF)
 Power:Power over Ethernet, IEEE802.3af, Class 0
 Local power, 12VDC,Idle 2W, Max 10W
 Auxiliary Contacts:1 Aux Output, dry contact
 Contact Ratings. Load: Resistive load
 Rated load:0.3 A at 125 VAC; 1 A at 30 VDC
 Rated carry current:1A
 Max.switching voltage:125 VAC,60VDC
 Max.switching current:1A

Audio Codes:G.711, G.722, G.729
 Network:10/ 100 BaseTX Ethernet, RJ45 connectors, Cat5e or better
 IP Protocols:IPv4, TCP, UDP, TFTP, RTP, RTCP, DHCP, SIP
 LAN Protocols:Power over Ethernet(PoE,802.3af), WLAN(IEEE 802.3af), Network Access Control(IEEE 802.1x),STP(IEEE 802. 1d), RSTP(IEEE 802. 1d-2004)
 Programming: Non-volatile flash memory programming and configuration through Web GUI
 Management and Operation:DHCP and static IP, remote automatic software upgrade, centralized monitoring, status LED
 Echo cancellation code:G. 167/G. 168

INSTALLATION





CERTIFICATION

RCM: AS/NZS CISPR 32

Australian communications:AS/CA S004

Australian Equipment-safety: AS/NZS 60950. 1:2015

EMC: EN50121 (Railway application-Electromagnetic Compatibility)



RoHS

PACKING



Unit size:2010*400*400mm Unit: N.W :70KG

SOLUTION



KNTECH Emergency Telephone Broadcasting System

