



## Handset T4

### Description

This handset is specially designed for telecommunication in noisy environments with a push-to-talk switch. Moreover, it can be made with a volume control button as per the customer's requirement

### Features

- 1 The handle shell is made of special PC/ABS antistatic and other engineering plastics.
- 2 One-piece structure, good sealing and flame retardancy. It will not break when knocked, deform when twisted, and will not burst at minus 40 degrees.
- 3 Color of plastic housing: conventional glossy surface, matte surface can be customized.
- 4 Magnets or reed switches can be installed in the handle.
- 5 The transmitter adopts an anti-noise transmitter (sensitivity is -72DB, resistance 9.5Ω).
- 6 The handle has a switch (PTT) function.
- 7 It adopts puncture-proof, high-fidelity transmitter and receiver, and anti-noise transmitter to ensure the call transmission characteristics of the matching phone, which meets the requirements of 4.2 of GB/T15279-2002.
- 8 It can be matched with hook H3, H8 etc.

Product parameters

| Ambient temperature      | -30~+50 °C |
|--------------------------|------------|
| Relative temperature     | 10%~95%    |
| Atmospheric pressure     | 80~110KPa  |
| Ambient noise            | ≤100dB     |
| Operating frequency      | 300~3400Hz |
| Transmit loudness rating | 5~15dB     |
| Receive loudness rating  | -7~2dB     |
| Sidetone masking rating  | ≥7dB       |

Packaging details



Web: [www.koontech.com](http://www.koontech.com)

Email: [marketing@koontech.com](mailto:marketing@koontech.com)

Tel: (HK Office) +852 9068 2799 / (Shenzhen Office) +86 755 2744 8753

Shenzhen Office: T3 1001, Yifang Center, Baoan, Shenzhen, China

HK Office: HongKong Office: Unit 2C, 2nd Floor, Ka To Factory Building 2, Cheung Yue Street, Kowloon, Hong Kong

Factory: KNTECH Building, Phoenix Mountain, Limhai Zone, Shajiao Community, Humen, Dongguan, China