

## Network SIP Speaker Model: KNSIPSP-L4-15W



- > Clear, long-range speech
- > Simple installation with network cable
- > Supports SIP (VoIP)
- > Clear and simple

KNSIPSP-L4-15W Network Horn Speaker is a simple-to-install outdoor loudspeaker that provides clear, long-range speech for remote speaking in video surveillance applications.

In live monitoring situations, KNSIPSP-L4-15W enables an operator to remotely address people and deter unwanted activity. The loudspeaker can also play a pre-recorded audio file when it is manually or automatically triggered in response to an alarm event.

KNSIPSP-L4-15W makes announcements possible from any- where with network connectivity. It easily integrates Voice over IP (VoIP) telephony systems that use SIP (Session Initiation Protocol).



The outdoor-ready KNSIPSP-L4-15W is easy to install. The loudspeaker has a built-in amplifier and supports over Ethernet . It connects directly to an IP network with one network cable for communication. It is powered supply by POE. KNSIPSP-L4-15W enables a high sound pressure exceeding 109~125 dB. Being a standalone unit, KNSIPSP-L4-15W can be placed anywhere, enabling a flexible, scalable and cost-effective approach to system design.






The speaker comes with pre-recorded audio files and allows users to upload their own audio.

Audio	
Audio streaming	One-way/ (Differential output)
Audio compression	G.711 PCM 8 kHz, G.726 ADPCM 8 kHz,
Audio input/output	Built-in microphone (can be disabled mechanically)
Built-in microphone specification	50 Hz - 16 kHz
Speaker	
Max sound pressure level	>125 dB/30W/1m
Frequency response	300 Hz-8 kHz
Coverage pattern	70° horizontal by 100° vertical (at 2 kHz)
Amplifier	
Amplifier description	Built-in 15W Class D amplifier
Supported protocols	IPv4/v6, HTTP, SIP, NTP, TCP, UDP, DHCP

General	
Casing	Impact-resistant aluminum, IP66-and NEMA-rated. For repainting instructions and impact on warranty, contact your partner
Memory	256 MB RAM, 256 MB Flash
Power	Power over Ethernet (POE) IEEE 802.3af/802.3 at Type 1 Class 3 (max 12.95 W)
Connectors	RJ45 10BASE-T/100BASE-TX POE
Operating conditions	-30°C to 70°C (-4F to 122F) Humidity 10-100% RH (condensing)
Approvals	
Dimension	280*205*290 mm

**Dimension:**



Key to symbols used	
	Weatherproof
	IP rating EN 60529
	100V line
	Low impedance
	Double insulated



*infinite possibility*

Web: [www.koontech.com](http://www.koontech.com)

Email: [marketing@koontech.com](mailto:marketing@koontech.com)

Tel: (HK Office) +852 9068 2799 / (Shenzhen Office) +0086 0755 2744 8753

Shenzhen Office: T3 1001, Yifang Center, Baoan, Shezhen, China

HK Office: Unit C5, 11/F, Ka To Factory Building, 2 Cheung Yue Street, Cheung Sha Wan, Kowloon, Hong Kong

Factory: KNTECH Building, Phoenix Mountain, Limhai Zone, Shajiao Community, Humen, Dongguan, China