

KNTD-100

UC features for up to 100 users

The KNTD-100 IP PBX appliance is designed to bring leading edge voice, video, data, and ability features to enterprises, small and medium businesses, retail and residential environments in an easy-to-manage fashion. This enterprise-grade on premise IP PBX supports E1, SIP Trunk, RJ45 networks and offers scalability by supporting up to 100 users. This secure and reliable IP PBX delivers unified communication features at an unprecedented price point it hout any licensing fees, costs-per-feature, or recurring fees. Host Standby N+1 redundancy System design.

KNTD-100 server is a computer device that centrally processes and manages information, with multiple functions such as storing, processing, sharing, and protecting data.

The KNTD-100 server can be equipped with three major systems: telephone, broadcasting, and access control, and has efficient and stable performance to meet your various needs.



100 users Supports up to 100 users, 20 SIP trunkacCounts, up to 10 concurrent calls.



Supports IVR (Interactive VoiceResponse).



Three-In-One Optional, Telephone system, Broadcasting system, Access control system.



Built-in call recordingserver recordingsaccessed via webuser interface.



Strongest-possible security protectionusing



Supports call queue for efficient call volume management.





HONGKONG KOON TECHNOLOGY LIMITED KNTD-100

	Technical Parameter	Konca	
Model	KNTD-100 IP PBX Enterprise - class unified communication system Hardware interface		
	Host Standby N+1 redundancy System design		
Network Interface	RJ45 Gigabit interface (10/100 / 1000M Ethernet adaptive)		
Reset switch	Support, Web configuration		
	Audio / video capability		
Speech algorithm	G.711, 7.29, 7.23,7.26 encoding		
Voice	G.711 A-law/ U-law, G.723.1, G.726, G.729A		
Video coding	H.264.		
	Signaling protocol		
DTMF detection method	Support RFC2833, SIP INFO		
Digital signal	SIP2.0		
Terminal management and automatic deployment capabilities	Support for SIP terminal plug -and-play auto-deploym support Remote upgrade,local upgrade)	nent (including DHCP / multicast SIP ,	
Network protocol	TCP UDP IP, RTP DHCP,SSH,HTTP,SIP		
	Safety		
Advanced defense	Alert events, whitelists, blacklists		
	Physical characteristics		
Global universal power supply	Input: 100~ ~ 240VAC, 50 / 60Hz;		
weight	Equipment weight: 3.5 Kg; Package weight: 4,4Kg		
Use the environment	Operating environment:32 -113° F/0~ 45° C, humidity (No condensation) Storage environment: 14-140°F / - 10 ~~ 60° C, humid (No condensation)		
Size	430mm(L)X246.7mm(W)X 44.3mm(H)IU standard		
Installation	Desktop or cabinet installation		



HONGKONG KOON TECHNOLOGY LIMITED KNTD-100

Additional features

Multi language support	Web user interface supports English / Simplified Chinese, customizable IVR / voice prompts in English, Chinese
Caller ID	ETSI-DTMF
Call Center	Supports call queues.
Customize Auto	Supports VR (Interactive Voice Response)
Concurrent call	Up to 100 SIP terminals can be registered, up to 20 concurrent calls
Members	Calls waiting, Call transfer, Ringing group, Subgroup, meeting, broadcast, blacklist, call / intercom, etc

KNTECH IP PABX MODEL NUMBER

REGISTER USER	SIMULTANEOUS CALLS	MODEL NUMBER
50 line	10 line	KNTD-50
100 line	20 line	KNTD-100
200 line	40 line	KNTD-200
300 line	60 line	KNTD-300
500 line	100 line	KNTD-500
800 line	160 line	KNTD-800
1000 line	200 line	KNTD-01K
3000 line	600 line	KNTD-03K
5000 line	1000 line	KNTD-05K





HONGKONG KOON TECHNOLOGY LIMITED KNTD-100

Voice dispatch-Telephone call













