

Product description



KND26 LED beacon with 72 pcs high brightness LED lamp and intelligent IC control function, shade with focus function, more flash brightness, better quality, running stabler. Used in electrical power, telecommunications, machine tools, shipbuilding, printing, mining machinery and other equipment for indication signal, notice the signal, accident signal.

Dimensional Drawing



Product Parameter

Power Consumption : 15W-23W

Voltage: AC110V-240V/DC12V/DC24V

Operating Temperature: -30 C-60 C

Color Optional: Blue,

Lamp Beads: $\Phi 5$ straw hat lamp LED

Operating Mode: Strobe

Material: Import highly transparent Carbonate Material

Fix type: Screw type + Magnetic

IP rating : IP66

Packing (package)

1.) Packing: red neutral packing

2.) Quantity: 30 pieces/piece

3.) Outer box size: 57.5*35.3* 37.5CM

4.) Weight: 8.5KG

The power cord (Enclosure) :

Material requirements: cable

Material requirements: cable

Cable: 0.5 square meters/length 200mm

Cable: 0.5 square meter/200mm long Power cable

(Enclosure):

Material requirements: cable

Material requirements: cable

Cable: 0.5 square meters/length 200mm

Cable: 0.5 square meter/200mm long



The shell (Enclosure) :

Material requirements :PC

Material requirements: PC



LED lamp bead (Enclosure) :

Lamp bead type: 20 (3528)

Lamp type: 20particle (3528)

Lamp bead color: pure blue

Lamp color: pure blue



The base (Enclosure) :

Material requirement: ABS

Material requirements: (ABS)

2. Input characteristics

(Input voltage range. from 1 10Vac to 130Vac, single phase AC input):

	Minimum	Maximum
Input Voltage	110VAC	240VAC

3. Input current

(Input current range: from 8 watts to 10 watts)

	Minimum	Maximum
DC input current	8w	10w

4. Order details

Model Number	Input voltage
KND26-DC-12V	DC12V
KND26-DC-24V	DC12V
KND26-AC-110V240V	110V240V

5. Color details



6. Environmental requirement

3.1 Operating Temperature:

-25°C~ +65°C, full load, normal operation (Full load Normal operation).

-25°C~ +65°C, Full load Normal operation.

3.2 Storage Temperature: -20°C to 85°C, with package.

3.3 Working humidity (Relative Humidity):

5%(0°C)~90%(40°C), 72 hours, full load, normal work

5%(0°C)~90%(40°C)RH, 72Hrs, Full load Normal operating.

3.4 Altitude work requirements (Altitude):

When working: less than or equal to 2000 meters Operating: ≤2000 meters

In storage: less than or equal to 2000 meters Non-operating: ≤2000meters

3.5 Dropping (Packed):

PC shell, ABS base, internal screws, LED SMD lamp beads.

PC case, ABS base, internal screws, LED SMD lamp beads.

Height: 76cm

wooden board

Lights are normal, no case cracked.

lamplight is normal, no shell rupture

7. Installation details



8. Packaging details

- 1.) Packing method: red neutral packing
- 2.) Quantity: 30pcs/piece
- 3.) Outer box size: 57.5*35.3*37.5 CM
- 4.) Weight: 8.5KG