

## VoIP Video Intercom

### KNZD-70

Unit size: 340\*330\*70mm

Weight: 5.2kg

Power Supply: PoE or DC/AC110-240V



Wall Mounting Type



Flushed Mounting Type



### Main Feature

Industrial grade SIP high-definition two-way video intercom telephone

Independent research and development and production

SUS316 stainless steel shell

IP66 waterproof protection

Industrial grade telephone PCB board

High-Low temperature adaptation  $-40^{\circ} + 75^{\circ}$

12 flat stainless steel keypad

PA loudspeak function

With waterproof backlit emergency call button

**Acquaint KNZD-70**

VOIP Telephone BI-Directional Video telephone Scratch resistant, HD Screen  
SIP supports 5 SIP servers SIP 2.0 Support TR069  
7" digital TFT-LCD of 1024 x 600 pixels with Visual angle adjustable display screen  
sensor camera with 5Mega pixels 2xLAN, PoE, USB  
TWO group of speed dial for emergency call. Protection: About IP65  
Speaker: 8 ohm 1.5W, loudness 85dB(A) to 65dB(A) MIC's working distance 80cm  
Ring: >95dB. Coverage 1.5m radius  
The call button is flash when ring, lighting during a call, off when standby.  
HD voice with high quality headset/HD voice in speakerphone mode

**TFT Screen features**

Voice Codecs: G.711a/u, G.7231 high/low, G.729a/b, G.722, G.726, iLBC, AMR-NB;  
AMR-WB  
Video codecs:H.263, H264, MPEG4 Video resolution: QCIF,CIF,QVGA  
Photo Format: PEG GIF and BMP PNG Video formats: MP4, 3 GP and FLV  
Echo cancellation: G.168 compatible with the LEC, including hands-free(AEC)  
VGS, VAD,CNG,Jitter buffer Speakerphone full-duplex  
Possibility of registering a domain or implementation of SIP calls Peer to peer  
Support for STUN Support for the SIP SMS Adjusting the volume in all modes  
(headset/ hands-free/ headset wire/ bell) Contrast : 1000 : 1  
Brightness : 450cd/m<sup>2</sup>  
Viewing Angle : 178 degrees horizontal / 178 degrees vertical (at contrast ratio 10:1)  
Screen orientation Portrait instead of landscape.


**Spe of Built-in induction loop**

With induction loop coverage 1M radius.  
Supply voltage: 12V DC  
Max operation current: 3A  
Inputs: internal electret microphone, suitable line level/second microphone  
Microphone: sensitivity: 66Dbm to -2dbm Bandwidth 50Hz to 20Khz  
Overail Performance: bandwidth at any output level 50hz to 15khz Distortion:<0.5%  
TGD@1KHZ  
DYNAMIC RANGE:>90db Noise:<-86db CMRR:>84DB  
Coverage(internal loop)1m radius Input level control Mic:-40+40db  
Power output: current0.8ARMS @1KHZ 3.0apeak


Quality: Tested to and conforms with BS7594 and BS6.83 PART 4, en60118-4

Power consumption: standby 25ma (0.04w) Maximum in use 1.5A(9W)

### Wall Mounting Type



### Flushed Mounting Type



### Packing Details

Kntech standard carton packing

Unit size: 340\*330\*70mm

Weight: 5.2kg

Packing carton size: 46\*41\*49cm/4pcs

N.W.: 19.8kg

G.W.: 21.9kg