



VoIP KNZD-16 Help Phone

DESCRIPTION ITEM NO.ZD0160022

1. Working with HUAWEI, AVAYA, ALCATEL, MITEL, 3CX, etc
2. When ON/OFF active with dry contact signal output for CCTV interface
3. Stainless steel 304 body, vandal & tamper-resistant hardware, easy installation
4. Waterproof rating IP55 dust proof
5. Built-in loud speaker 3W
6. Hands-free button, auto-answer and auto-hang up
7. Wall mounted installation, flush mounted optional
8. POE power supply or DC12V powered
9. Service temperature range from -40 degree to +70 degree
10. Support echo cancellation, built-in induction loop optional
11. Remote software upgrade, configuration and monitoring
12. Optional 7 minute time out to release the line. (This function upon buyer's requirement)
13. Body in electrophoresis process finish no fingerprint, resistant to corrosion
14. Application: Metro, railway, LRT, speedway, airport, bank, university, hotel, supermarket and pedestrian areas in cities etc



SPECIFICATION

VoIP SIP2.0 telephone	DTMF dialing	Audio Codes:G.711, G.722, G.729
MTBF:100000hours	MTTR: 2 hours	Network:10/100 BaseTX Ethernet, RJ45 connectors, Cat5e or better
Hotline(maximum length of each number is 16 digits)		IP Protocols:IPv4, TCP, UDP, TFTP, RTP, RTCP, DHCP, SIP
Communication: Full duplex 2-way hands-free communication		LAN Protocols:Power over Ethernet(PoE,802.3af), WLAN(IEEE 802.3af), Network Access Control(IEEE 802.1x),STP(IEEE 802.1d), RSTP(IEEE 802.1d-2004)
Call Control Signaling:VOIP SIP Info(DTMF), RFC 2833(DTMF)		Programming:Non-volatile flash memory programming and configuration through Web GUI
Power:Power over Ethernet, IEEE802.3af, Class 0 Local power, 12VDC,Idle 2W, Max 10W		Management and Operation:DHCP and static IP, remote automatic software upgrade, centralized monitoring, status LED
Auxiliary Contacts:1 Aux Output, dry contact		Echo cancellation code:G.167/G.168
Contact Ratings. Load: Resistive load		
Rated load:0.3 A at 125 VAC; 1 A at 30 VDC		
Rated carry current:1A		
Max.switching voltage:125 VAC,60VDC		
Max.switching current:1A		

CERTIFICATION

RCM: AS/NZS CISPR 32 Australian communications:AS/CA S004
Australian Equipment-safety: AS/NZS 60950.1:2015
EMC: EN50121(Railway application-Electromagnetic Compatibility)



PACKING



INSTALLATION

Unit size: 560*195*38mm	Unit: N.W: 2.76KG
1pcs packing box size: 640*275*185mm	Unit G.W: 3.5KG
2pcs in 1 outer carton box: size: 790*190*320mm	G.W: 6.5KG

INSTALLATION

