



Analogue KNZD-16 Metro Help Phone

DESCRIPTION ITEM NO.:ZD0160012

1. Stainless steel 304 body with SUS hands free button.
2. Waterproof rating IP55 dust proof.
3. Hands-free, built-in loudspeaker.
4. With built-in induction loop optional.
5. Telephone line powered, if with induction loop, extra power supply needed.
6. Service temperature range from -30 degree to +75 degree.
7. Lightning protection to ITU-T recommendation K.21.
8. Support hotline calling.
9. Support echo cancellation, wall mounted installation, flush mounted optional.
10. Optional 7 minute time out to release the line. (This function upon buyer's requirement)
11. Body in electrophoresis process finish no fingerprint, resistant to corrosion
12. Application: Metro, railway, LRT, speedway, airport, bank, university, hotel, supermarket and pedestrian areas in cities etc



SPECIFICATION

1. PSTN analogue telephone
2. DTMF dialing
3. MTBF:100000hours
4. MTTR: 2 hours
5. Connection: RJ11 screw terminal pair cable
6. Applicable for various types of SPC exchange PABX and dispatching exchange system with feeding voltage of 33-60V.
7. Ambient temperature:-30 ~ +60 degree. Relative humidity:10%~95%
Atmospheric pressure: 86~106Kpa Circumstance noise:less than 60dB(A)
8. Sound level of ringing:over 70dB(A).
9. Standard frequency:low frequency group:697. 770. 852. 941Hz,
high frequency group:1209. 1336. 1477Hz, frequency deviation:-1.5% ~ +1.5%
10. Call transmission index:(5KM)SLR<12,RLR<-1,STMR>10, output impedance is 600 Ohm.
maximum distance: 7KM
11. Hotline setting (maximum length of each number is 16 digits)
12. Connection: RJ11 screw terminal pair cable (or RJ11 Socket of plug upon request)
with stainless steel cable protected

CERTIFICATION

EN55022: emissions

EN55024: immunity

Ingress Protection: GB4208-93 IP66 FCC

ITU-T Recommendations K21

EMC: EN50121(Railway application-Electromagnetic Compatibility)

**RoHS****PACKING**

Unit size:560*195*38mm Unit: N.W:2.76KG

1pcs packing box size: 640*275*185mm Unit G.W:3.5KG

2pcs in 1 outer carton box: size: 790*190*320mm G.W:6.5KG

**HONGKONG KOON TECHNOLOGY LTD**TEL:0086755 29790158/27448753 Fax:0086755 29790278
Email:marketing@koontech.com www.koontech.com

INSTALLATION

