

Product name: KNTECH desktop intercom telephone

Product model: KNZD – 59

Product material: 304 stainless steel

Waterproof level: IP65

Size: 280 *193.2 *86.1 mm

Installation method: desktop type

Install screws: no

Product picture:



Product introduction:

1. Strong compatibility of the system extended, support standard SIP 2.0 (RFC3261) and related RFC agreement;
2. Support one bottom call the dispatcher station, host, specify the terminal;
3. Support digital keyboard;
4. Support three shortcuts keypad;
5. Provides alarm, monitor, intercom, broadcast function;
6. full-duplex talk functions;
7. Use advanced echo elimination technology;
8. Application: show Caller id, Contacts.
9. Speakers and microphone sensitivity adjustable;
10. Optional G. 729, G. 723, G. 711, G. 722, G. 726 and many ways of voice coding;
11. System provides the recording and query the recording files at any time;

12. Setting via a WEB interface;
13. Online software upgrade;
14. Support power 1 w;

Communication protocol	SIP 2.0(RFC-3261)	
Chip	Broadcom1190	
Keypad	Design	Stainless steel
	Number	Full digital keypad, 3 shortcut (customizable), one hands-free button
Display	Screen	1 pcs
Voice	Hands-free microphone	1 pcs
	Amplifier	3W
	Speaker	3W
	Onboard power amplifier bypass jump line	Support
	Volume control	Adjustable
	Full duplex hands-free	Support (AEC)
	Head phone jack	Support
	Handset jack	Support
Voice stream	Support protocol	RTP
	C-Codec	G.729,G.723,G.711,G.722,G.726
Connection	Power supply	5V-15(+/-15%)/1A DC or PoE
	PoE(IPGB-1verion not support)	PoE 802.3af(Class1)48V
	LAN	10/100BASE-TX s Auto-MDIX, RJ-45
	WAN	10/100BASE-TX s Auto-MDIX, RJ-45
	Recommend cable	Cat5e or higher

	LCD	Support (optional)
	RS232	Aluminum cover ,aluminum bottom case
	Shell material	aluminium alloy for the surface cover and the back shell
	Working temperature	Zero to fifty-five degrees

Dimension:

