



VOIP KNZD-05LCD Prison Phone

DESCRIPTION ITEM NO.ZD0050022

1. Cold-roll steel body, vandal & tamper-resistant hardware, easy installation.
2. Waterproof rating IP55 dust proof.
3. Full keypad with memory, 10 button programmable telephone, support free dial.
4. Magnetic reed hook-switch, with LCD display.
5. Lightning protection to ITU-T recommendation K.21.
6. Heavy duty handset with hearing aid compatible receiver, noise canceling microphone.
7. Handset with industrial strong metal cord.
8. POE power supply or DC12V.
9. SUS keypad keep waterproof and dusty proof.
10. Temperature range from -40 degree to +70 degree.
11. Support echo cancellation, wall mounted type.
12. Remote software upgrade, configuration and monitoring.
13. Optional 7 minute time out to release the line if the handset is left off hook. Optional
14. Powder coated in UV stabilized polyester finish.
15. The housing covered with a layer of reflective label for easy identification at night. Optional
16. Application: Prison, bank, airport, school, metro, railway station, LRT, hotel, supermarket and pedestrian areas in cities etc.



SPECIFICATION

| | | |
|---|---------------|--|
| VoIP SIP2.0 telephone | DTMF dialing | Audio Codes:G.711, G.722, G.729 |
| MTBF:100000hours | MTTR: 2 hours | Network:10/100 BaseTX Ethernet, RJ45 connectors, Cat5e or better |
| Free dial (maximum length of each number is 16 digits) | | IP Protocols:IPv4, TCP, UDP, TFTP, RTP, RTCP, DHCP, SIP |
| Communication: Full duplex 2-way hands-free communication | | LAN Protocols:Power over Ethernet(PoE,802.3af), WLAN(IEEE 802.3af), Network Access Control(IEEE 802.1x),STP(IEEE 802.1d), RSTP(IEEE 802.1d-2004) |
| Call Control Signaling:VOIP SIP Info(DTMF), RFC 2833(DTMF) | | Programming:Non-volatile flash memory programming and configuration through Web GUI |
| Power:Power over Ethernet, IEEE802.3af, Class 0 Local power, 12VDC,Idle 2W, Max 10W | | Management and Operation:DHCP and static IP, remote automatic software upgrade, centralized monitoring, status LED |
| Auxiliary Contacts:1 Aux Output, dry contact | | Echo cancellation code:G.167/G.168 |
| Contact Ratings. Load: Resistive load | | |
| Rated load:0.3 A at 125 VAC; 1 A at 30 VDC | | |
| Rated carry current:1A | | |
| Max.switching voltage:125 VAC,60VDC | | |
| Max.switching current:1A | | |

CERTIFICATION

RCM: AS/NZS CISPR 32 Australian communications:AS/CAS004
Australian Equipment-safety: AS/NZS 60950.1:2015
EMC: EN50121(Railway application-Electromagnetic Compatibility)

**PACKING**

Unit size:280*150*130mm Unit: N.W:2.37KG
1pcs packing box size: 320*190*190mm Unit N.W:2.37KG Unit G.W:2.9KG
6pcs in 1 outer Carton box: size: 510*370*390mm N.W:14.22KG G.W:18.44KG



INSTALLATI

