



Front door glass door  
Rear door sheet metal door

- KL series cabinet features a single open white tempered glass front door;
- Single sheet metal rear door;
- The front and rear doors have a welded reinforcement structure, which is aesthetically pleasing and sturdy;
- Equipped with high-end and elegant locks on the front and rear doors;
- Can be equipped with various locks required by customers;
- The front and rear doors can be changed to double open.

Luxury equipment door lock	High quality cold rolled steel plate	Standard rack mounted Standard 19 inches	Quick disassembly and assembly of side door panel
Reinforcing rib structure	Square hole bar 2.0N	Protection level IP2	Load capacity 800kg

**Cabinet height:** please refer to the size specification comparison table for details;

**Thickness of square hole strip:** 2.0MM

**Static load capacity:** 800KG (with bracket)

**Installation beam thickness:** 1.5MM

**Material of square hole strip:** fingerprint resistant aluminum zinc coated plate

**Other materials:** spcc high-quality cold-rolled steel plate

**Protection level:** IP20

**Other thicknesses:** 1.2MM

**Executive standards:** comply with ANSI/EIA RS-310-D, IEC297-2, DIN41494; PART1; DIN4 149 4; PART7、GB/T3047.2-92; Compatible with ETSI standards.

**Surface treatment:** square hole strip, installation beam: aluminum zinc plate; others: degreasing, silane treatment, electrostatic spray molding

## Dimensional Specification Comparison Table

If you need other models, please consult customer service.

Cell color definition:   Promotional Products;   Standing specifications;

  predefined specification;

The specification codes in this table are incomplete. Please provide the requirements when placing an order.

height Width/Depth		18U (988mm)	22U (1166mm)	27U (1388mm)	32U (1610mm)	37U (1833mm)	42U (2055mm)	47U (2277mm)
	600 (mm)	6618	6622	6627	6632	6637	6642	6647
	800 (mm)	6818	6822	6827	6832	6837	6842	6847
height Width/Depth		18U (988mm)	22U (1166mm)	27U (1388mm)	32U (1610mm)	37U (1833mm)	42U (2055mm)	47U (2277mm)
600 (mm)	600 (mm)	6618	6622	6627	6632	6637	6642	6647
	800 (mm)	6818	6822	6827	6832	6837	6842	6847
	900 (mm)	6918	6922	6927	6932	6937	6942	6947
	1000 (mm)	6018	6022	6027	6032	6037	6042	6047
	1100 (mm)	6118	6122	6127	6132	6137	6142	6147
	1200 (mm)	6218	6222	6227	6232	6237	6242	6247
800 (mm)	600 (mm)	8618	8622	8627	8632	8637	8642	8647
	800 (mm)	8818	8822	8827	8832	8837	8842	8847
	900 (mm)	8918	8922	8927	8932	8937	8942	8947
	1000 (mm)	8018	8022	8027	8032	8037	8042	8047
	1100 (mm)	8118	8122	8122	8132	8137	8142	8147
	1200 (mm)	8218	8222	8222	8232	8237	8242	8247

## Factory included accessories



Layer by layer; **X3** units  
(1 layer board for cabinets below 37U)



One PDU socket



4 brackets



1 fan unit  
(equipped with 2 units for depths above 600mm)



One hexagonal wrench



Four casters



40 hexagonal screws



1 factory certificate

## Picture display

