



**Highway Emergency Phone****ZD09A0012****DESCRIPTION**

1. Cold-roll steel body with SUS handsfree button.
2. Waterproof rating IP55 dust proof.
3. Stainless steel button, double loudspeaker.
4. Weather resistant to IP55 standard, service temperature range from -30 degree to +75 degree.
5. Lightning protection to ITU-T recommendation K.21.
6. Support hotline calling.
7. Phone integrity wiring to enable the telephone system to check if the telephone unit is still Operational.(If PABX have this available we can provide this function).
8. Optional 7 minute time out to release the line if the handset is left off hook. This function upon buyer's requirement).
9. Powder coated in UV stabilized polyester finish.
10. The housing covered with a layer of reflective label for easy identification at night.Optional
11. Application: Tunnel, metro, railway, LRT, speedway, marine, ship,offshore, mine, power plant, bridge etc.

SPECIFICATION

1. PSTN analogue telephone
2. DTMF dialing
3. MTBF:100000hours
4. MTTR: 2 hours
5. Connection: RJ11 screw terminal pair cable
6. Applicable for various types of SPC exchange PABX and dispatching exchange system with feeding voltage of 33-60V.
7. Ambient temperature:-30 ~ +60 degree. Relative humidity:10%~95%
Atmospheric pressure: 86~106Kpa Circumstance noise:less than 60dB(A)
8. Sound level of ringing:over 70dB(A).
9. Standard frequency:low frequency group:697. 770. 852. 941Hz,
high frequency group:1209. 1336. 1477Hz, frequency deviation:-1.5% ~ +1.5%
10. Call transmission index:(5KM)SLR<12,RLR<-1,STMR>10, output impedance is 600 Ohm.
maximum distance: 7KM
11. Hotline setting (maximum length of each number is 16 digits)
12. Connection: RJ11 screw terminal pair cable (or RJ11 Socket of plug upon request)
with stainless steel cable protected

INSTALLATION**CERTIFICATION**

EN55022: emissions

EN55024: immunity

Ingress Protection: GB4208-93 IP66 FCC

ITU-T Recommendations K21

EMC: EN50121(Railway application-Electromagnetic Compatibility)

**RoHS****PACKING**

Unit size:300*180*95mm Unit: N.W:4.2KG

1pcs packing box size: 439*277*191mm Unit N.W:4.2KG Unit G.W:5KG

6pcs in 1 outer Carton box: size: 730*390*340mm N.W:31.8KG G.W:34KG

Web: www.koontech.comEmail: marketing@koontech.com

Tel: (Shenzhen Office) +86 755 2744 8753 / (HK Office) +852 9068 2799

Shenzhen Office: 1001 Block A Building T3,Yifang Center, Bao'an, Shenzhen, Guangdong, China

HK Office: Unit C, 2/F, Ka To Factory Building, 2 Cheung Yue Street, Cheung Sha Wan, Kowloon, Hong Kong

Factory: KNTECH Building. Phoenix Mountain, Limhai Zone, Shajiao Community, Humen, Dongguan, China