

VOIP-SIP IP Video INTERCOM ROBUST



Robust IP INTERCOM

- *Super good sound clarity during conversation
- *Support standard Session Initiation Protocol(SIP), RFC 3261
- *Remote software upgrade, configuration and monitoring
- *Power over Ethernet(PoE,802.3af), local 12V DC
- *IP66 vandal resistant marine grade stainless steel faceplate
- *LED indicator
- *Echo cancellation
- *Password, RFID card, Video, Remote program



Model		KNZD-52V
Material		Robust aluminum alloy die-cast body stainless steel faceplate
Dimensions(W*H*D)		Unit size: 235*131*78.7mm; Carton size each box:32.5*18*13.5cm/G.W.: 2.3kg
Weight		2.3kg
Operating Temperature		-40°F to +158°F/ -40°C to +70°C
Relative Humidity		Up to 95% non-condensing
Protection		IP66, vandal-resistant and water-resistant design
Communication		Full duplex 2-way hands-free communication
Call Control Signaling		SIP(RFC compliant), SIP Info(DTMF), RFC 2833(DTMF)
Audio Codes		G.711, G.722, G.729
Camera	Image Sensor	OV9712
	Total Pixels	480P 15fps
	Min. illumination	0.1lux
	Field of view	150° horizontal Opposite angles 170°
	Lens	2.75mm
	Framerate	15fps, 30fps, MJPEG, H.264
	Streamine	Dual-stream at different frame rate and bandwidth
	ONVIF compliant	Yes
Power		Power over Ethernet, IEEE802.3af, Class 0 Local power, 12VDC,Idle 2W, Max 10W
Auxiliary Contacts		1 Aux Output, dry contact Contact Ratings Load: Resistive load Rated load:0.3 A at 125 VAC; 1 A at 30 VDC Rated carry current:1A Max.switching voltage:125 VAC,60VDC Max.switching current:1A
Network		10/100 Base TX Ethernet, RJ45 connectors, Cat5e or better
IP Protocols		IPv4, TCP, UDP, TFTP, RTP, RTCP, DHCP, SIP
LAN Protocols		Power over Ethernet(PoE,802.3af), WLAN(IEEE 802.3af), Network Access Control(IEEE 802.1x), STP(IEEE 802.1d), RSTP(IEEE 802.1d-2004)
Programming		Non-volatile flash memory programming and configuration through Web GUI
Management and Operation		DHCP and static IP, remote automatic software upgrade, centralized monitoring, status LED
Echo cancellation code		G.167/G.168

Kntech standard export carton packing

Unit size: 235*131*78.7mm; N.W.: 2.3kg;
1pc carton:32.5*18*13.5cm; N.W.: 2.3kg; G.W.: 2.6kg 4pcs carton: 37*35*
27cm; G.W.: 8.7kg

Size & Packing

