

## Ceiling Speaker

Model: KNL12


### Specification

Model No	KNL12
Rated Voltage	Constant Voltage Mode:70/100V
Rated Power	Constant Voltage Mode Power Taps @ 70V: 1.5W / 2.5W / 3.5W / 5W / 7.5W Power Taps @ 100V: 3W / 5W / 7W / 10W / 15W
Size (mm)	Φ 203 * 104 (H)
Material	ABS & Metal Mesh Cover
Mounting	Ceiling Mounted
Audio Port	2 Pin Terminal Audio Input
Frequency Response	90 Hz ~ 20kHz
Sensitivity	90 ± 2dB SPL/1W/1m
Max. Sound Pressure Level (Rated 1W / 1m)	98 ± 2dB
Coverage Angle (-6dB) (°)	120
Operating Temperature Range (°C)	-20 to 50
Speaker size	1 x 3-inch/75-mm woofer (Low Frequency ) 1 x 0.75-inch/19-mm neodymium dome tweeter (High Frequency)
Speaker Input Configuration	8 ohms
Net Weight	1.15kG

Gross Weight	1.6kG
Humidity	<95%
Rustproof detail	Rustproof
Certification	Certified Compliance With EN 54-16 and ISO 7240-16 Standard, CE Marked / IEC 61082/ IEC 60300/ IEC 60068 IEC 60050/ IEC 62368/ IEC 60601-1 and IEC60601-1-2
Application	Home theater, conference room, tea house, coffee shop, high-end private club, etc.


## Dimensions

Unit: mm




## Connection Method


### ■ Constant Voltage Mode




### ■ Constant Resistance Mode



## Application Example



## Frequency Response Diagram



Web: [www.koontech.com](http://www.koontech.com)

Email: [marketing@koontech.com](mailto:marketing@koontech.com)

Tel: (Shenzhen Office) +86 755 2744 8753 / (HK Office) +852 3460 4652

Shenzhen Office: 1001 Block A Building T3, Yifang Center, Bao'an, Shenzhen, Guangdong, China

HK Office: Unit C, 2/F, Ka To Factory Building, 2 Cheung Yue Street, Cheung Sha Wan, Kowloon, Hong Kong

Factory: KNTech Building, Phoenix Mountain, Limhai Zone, Shajiao Community, Humen, Dongguan, China